







1 temperature cabinet

Large size

Premium Pack



Maturing cabinet, for ageing or serving wine



Technical Specifications

Temperature and

Capacity

106 or 124 maximum bottles*

Setting range from 6 to 18°C

·At 12°C, independently regulated hygrometry at 70%

Design

 Triple glazed and anti UV Full Glass door with argon gas. Not reversible. Right or left opening > Choice on order

Inner lighting: ambiance lighting by 4 LED under each shelf and 2 LED under the control panel (3 options: permanent, when opening door,disabled). 3 levels of light intensity · Handle integrated in the door profile

· LED screen with sensitive keys

·External frame in aluminum, black epoxy painted

· Antibacterial, rot-proof and fireresistant decoractive panels

Regulation and equipement

· Electronic regulation

· Internal display and settings

· Temperature display

· Hygrometry display,non adjustable.

· Display only at 12°C

- Alarms in case of dysfunction (open door, sensor fault, temperature dysfunction, hygrometry dysfunction, need to fill the humidity tank, need to replace charcoal filter)

· Default ECO mode (= screen saver) · Automatic defrost

·On/Off/ switch

· Active charcoal filter 150x150 mm

· 4 adjustable shock absorbing feet + 4 embellishments

· Condensate discharge pipe

· Autonomous hygrometry regulation tank «Hygrocontrol System». Patented system

· Frost protection thermostat

Covering **2 covering available**

Standard shelf

9 Bordeaux bottles

Sliding shelf ACMSR

7 Bordeaux hottles + 2

Magnum bottles





Mineral Grey

Red Farth

Accessories

· 11 sliding shelves + 1 fixed, with black tinted ash front

· Sliding shelves equipped with a soft close device

· 8 mains du Sommelier at the bottom of the cabinet

· 6 removable bottle identifiers per sliding shelf

· 1 erasable felt tip marker

· 1 key ring

· 1 microfiber cloth

Technologies Cold production:

Cords:

Mixed air/ Variable speed compressor R600a gas CE/US/UK/JA/AU/CH/C6

Heat production: Resistance **Heat release:** Automatic

Automatic 45W resistor

Aluminium

Exterior coating material:

Compact HPL panel (High pressure laminated) 12,5mm thickness

Insulation type:

Inner material:

Injected polyurethane foam (59 mm)





General features

	Full Glass door
Gross weight packaged (kg)**	340
Net weight cellar equipped (kg)	250
Dimensions H x W x D (mm)	1847 x 880 x 617***
Dimensions packaged (mm)	2000 x 970 x 700
Colours / Finishes	Red Earth, Mineral Grey

^{**}Equipped cellar weight ***+23mm with rear stop

Energy efficiency & Consumption

Cords	230V-50Hz	115V-60Hz	
Type of door	Full Glass	Full Glass	
Energy efficiency class	Е	/	
Annual energy consumption AEC (Kwh/year)	100	85	
Sound emission (dB(A))	34 (steady state)	34 (steady state)	
Sound emission Class	В	/	
Ambient operating temperature (°C)	5-35	5-35	
Useful volume (litres)	421		

For a "service" usage, with an inner temperature between 6-9°C, we recommend to not place Royale in an ambient environment above 30°C/70% HR.

Royale, in a few words...

Why Royale?

Quite simply because it represents the best we can offer our customers in terms of performance, durability and aesthetics.



